

# Araldite®

professional adhesives



## Araldite® Instant 24ml Syringe

**A strong, long lasting solvent-free adhesive which is water resistant and can be painted or sanded. Sets in 90 seconds.**

### Important

Bonds metal, wood, masonry, ceramics, glass, dry concrete, chipboard, leather, cardboard, fabric, rubber and most plastics (except polyethylene, polypropylene, Teflon®, expanded polystyrene).

Make sure surfaces are clean and free from dust, corrosion, dirt and grease.

For optimum bonding, slightly roughen surfaces with sandpaper and degrease metals with a suitable solvent.

During assembly apply light pressure to the joint until set (clamps, tape) around 4 minutes. Allow 2 hours to attain full strength before rough handling or sanding.



1 Snap off the resealable cap from between the syringe plungers and break off the end seal. Depress the plunger to dispense equal amounts of both components onto a clean disposable surface. Re-fit the cap to close the nozzle.

2 Mix thoroughly for at least 20 seconds until well mixed. Araldite® Instant remains usable for max. 90 seconds.

3 Make sure both surfaces are clean and dry. Apply to both surfaces of the joint.

4 Assemble carefully and remove any excess adhesive with a sharp blade once partially set.

### How to apply

Araldite® Instant is a strong 2-component epoxy adhesive with very fast setting. Sets clear. Oil, chemical and impact resistant. High temperature resistance (-30°C to 65°C).

Do not use to repair or bond items that will contact food or drink. Not recommended for bonding rear-view mirrors to car windscreens.

### Storage

Should be stored in a dry place at room temperature in the original syringe.

### New

Environmentally friendly product formulation plus eco-friendly packaging for easy recycling.