

DIRECTA

ESSENTIALS FOR INDUSTRY

Tel: 01621 828882

www.directa.co.uk

TECHNICAL DATA SHEET

PRODUCT: 2090 Painters Tape
Our Reference: 2090BUBU

Scotch- Blue Painters Tape for Multi- Surfaces ref 2090 is medium adhesion tape ideal for paint masking on multiple surfaces, including painted walls and trim, woodwork, glass and metal. It can be removed cleanly from the surface for up to 14 days even in direct sunlight.

Product Characteristic	Value
Backing	Crepe Paper
Adhesive	Acrylic
Standard roll length	60 Yards (54.8m)
Roll Width	50mm
Colour	Blue

Typical Physical Properties	Value	Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.
Adhesion to Steel	23 oz./in.	ASTM D-3330
Tensile Strength	27 lbs./in.	ASTM D-3759
Elongation at Break	7%	AST, D03759
Total Thickness	5.4 mils	ASTM D-3652

Feature (HAS)	Advantage WHICH MEANS)	Benefit (SO THAT)
Acrylic Adhesive	Adhesive Transfer Resistance	Sticks easily to the surface and stays intact upon removal/ reduces labor and rework
	Increased Light and UV Stability	Clean removal/ reduces labour
	Medium adhesion	Easy to use/ reduces labour
	Controlled Tack	Minimal adhesion build over time with clean and safe removal/ reduces rework and labour, and helps to produce high quality results
Crepe Paper Backing	Smoothness	Consistent surface contact and secure holding power
	Conformability	Easy handling/ helps reduce overall project time
	Strong	Removes from Surface without tearing
Backing Saturant	Easy Tear	Good handling/ helps reduce waste
	Solvent and Moisture Resistance	Resists paint bleed- through and adhesive doesn't soften or transfer when tape is wet
Back size Treatment	Controlled Unwind	Easy to use/ smooth unwind

Warnings:

Do not use with or on nitrocellulose lacquer coatings

Do not use on wallpapers, unpainted wallboard, wood floors or poorly bonded finishes.

IMPORTANT NOTICE: All statements, technical information and recommendations herein are based on tests we believe to be reliable. Directa does not warrant or guarantee the accuracy or completeness of this information. THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE: Directa's only obligation shall be to replace such whether this Directa product proved to be defective. User is responsible for determining whether this Directa product is for particular purpose and suitable for users method of application. Because there are many factors that can affect the use and performance of this product, some of which are uniquely within the users knowledge and control, it is essential that the user evaluate this product to determine whether it is fit for a particular purpose, is suitable for the users method of application, and meets the users performance specifications and expectations.

Limitation of Liability: Directa SHALL NOT BE LIABLE FOR ANY LOSE OR DAMAGES WHETHER DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL (INCLUDING BUT NOT LIMITED TO LOST PROFITS, BUSINESS OR REVENUES) WARRANTY OR STRICT LIABILITY. No statement or recommendation not contained herein shall have any force or effect unless contained in an agreement signed by a Directa officer...

DS708 .TDS

7 February 2012