

## Sparks Electrical Tape

**Ref: 007**

**Sizes: 12mm/15mm/19mm/25mm/38mm/50mm/  
75mm/100mm/150mm/200/300mm x 33M  
19mm x 20M  
19mm x 4.6M**



Product Name: 007/757/EFI 7			DATE:2021.07.15
Items	Unit	Spec. Value	Test Method
I. Dimension & Tolerances: Thickness:	mm	0.15±0.005	ASTM D-1000
Composition Backing: Glue:		Plasticized PVC Rubber base	
Physical & Chemical Prop: 180°			
Peel Adhesion:			
To Steel:	N/25mm	3.5 ↑	ASTM D-1000
Tensile Strength:	N/25mm	50 ↑	ASTM D-1000
Elongation:	%	200 ↑	ASTM D-1000
Voltage Resistance:	V	600	ASTM D-1000
Temperature Resistance:	°C	90	ASTM D-1000
Flame Retardant:		YES	
Storage:		23oC 65% R.H	
Condition:	Year	2	
Validity:			
Remark:			
<b>REACH Compliant</b>			
Complies with British Standards BS3924 31/90Tp, BS4J10, BS3887 (1991) Part 2 Category 1 and IEC 454-3-1.The tape is flame retardant falling into the self-extinguishing category of AFEA 4009 T6 specification and BS3924 (1978) Category.			
*Customers need to test and confirm for the actual operational requirement and purpose or inform us to supply the further introduction service.			
Above information is for reference only and should not be as inspection standard.			